



**Spotstar Miniature**  
**120V, 220V-230V and 277V**  
 LED Fixed Track Lighting, x1~x5 Lights



|             |  |      |
|-------------|--|------|
| Catalog #   |  | Type |
| Project     |  | Date |
| Prepared by |  |      |

**Fixed Track LED**

**LED Track Lighting**



**DESCRIPTION**

Spotstar Miniature offers superior output in a small, sleek design allowing spot beam to each object. Designed for optimized optical and thermal management in a slender diecast housing. It's designed to use a direct 3.5" & 4" J-Box

**SPECIFICATION**

| HOUSING        | STS-2200F  |         |
|----------------|--|---------|
| Wattage (Typ)  | 10W  | 15W     |
| Lumen (Typ)    | 700  | 1,050   |
| Efficacy (LPW) | 70 lm/W  | 70 lm/W |
| Beam Angle     | 25° / 40°  |         |
| CRI (Typical)  | 80, 90   |         |
| Color (+/-5%)  | 2700K, 3000K, 3500K, 4000K, 5000K                                  |         |
| Dimming        | Triac & 0-10V the both (Consult with factory for approved dimmers) |         |

**FEATURES and FUNCTIONS**

- One piece casted aluminum and heat sink designed to facilitate heat dissipation.
- Exchangeable reflector for beam angle, 25 and 40 degree.
- 120V~277V AC LED module integrated IC chip imbed on board.
- Triac dimming is standard.
- Directionally adjustable up to 90° tilt and 355° rotation to shot spotlight into multiple directions.
- Available in 1 light, 2 lights, 3 lights, 4 lights and 5 lights

**Listing**

- CSA-us Certificated
- State of California Title 24
- Energy star Approved & Listed

**Warranty**

- 5years of lamp life.

**ORDERING INFORMATION**

| Housing   | Watts  | CRI  | CCT      | Beam Angle | Finish               |
|-----------|--------|------|----------|------------|----------------------|
| STS-2200F | 10 10W | 8 80 | 27 2700K | 25 25°     | WH White<br>BK Black |
|           | 15 15W | 9 90 | 30 3000K | 40 40°     |                      |
|           |        |      | 35 3500K |            |                      |
|           |        |      | 40 4000K |            |                      |
|           |        |      | 50 5000K |            |                      |

\*Consult with factory for custom finishes

Example : STS-2200F-10-830-25-BK

-  -  -  -  -