


CMED

120V, 220V-230V and 277V

LED Ceiling Flush Mounted Luminaires



Catalog #		Type
Project		Date
Prepared by		

Flush Mount LED



* Available in glass diffuser.



CMED 312P (314P, 317P)



CMED 412 (414, 417)



CMED 511 (513, 515)



CMED 612 (614, 616)

FEATURES and FUNCTIONS

- 120V AC LED module with integrated IC chip imbed on board and 10-100% Triac dimming with most of leading and trailing edge dimmer switches in the market.
- Hard gauge metal back plate and the heat sink to facilitate heat dissipation.
- PC diffused lens delivers perfect light distribution.
- 90CRI Standard. Available in 2700K, 3000K, 3500K, 4000K and 5000K.
- Triac dimmable standard.

Listing

- CSA-us Certificated
- State of California Title 24
- Energy star Approved & Listed
- Damp location

Warranty

- 5years of lamp life.

SPECIFICATION

HOUSING	CMED 312P	CMED 314P	CMED 317P	CMED 412	CMED 414	CMED 417	CMED 511	CMED 513	CMED 515	CMED 612	CMED 614	CMED 616
Shade Diameter X Assembled Height(H)	11.8"(Ø) X 3-7/16"	14.6"(Ø) X 4-3/16"	17.7"(Ø) X 4-3/16"	11.3"(Ø) X 3-5/16"	14.6"(Ø) X 3-13/16"	17.7"(Ø) X 4-5/8"	11.3"(Ø) X 5-11/16"	13.4"(Ø) X 5-1/2"	15"(Ø) X 5-9/16"	11.8"(Ø) X 3-7/16"	13.8"(Ø) X 3-13/16"	15.8"(Ø) X 4"
Wattage (Typ)	15W	23W	34W	15W	23W	34W	15W	23W	34W	15W	23W	34W
Lumen (Typ)	890	1,200	2,000	950	1,300	2,000	950	1,300	2,000	950	1,300	2,000
Efficacy (LPW)	59 lm/W	52 lm/W	59 lm/W	63 lm/W	57 lm/W	59 lm/W	63 lm/W	57 lm/W	59 lm/W	63 lm/W	57 lm/W	59 lm/W
CRI (Typical)	80, 90											
Color (+/-5%)	2700K, 3000K, 3500K, 4000K, 5000K											
Dimming	Triac(Consult with factory for approved dimmers)											

ORDERING INFORMATION

Housing	Watts	CRI	CCT	Diffuser	Finish
CMED 3XXP 12", 14", 17"	15 15W	8 80	27 2700K	P Plastic	WH White
CMED 4XX 12", 14", 17"	23 23W	9 90	30 3000K	G Glass	BK Black
CMED 5XX 11", 13", 15"	34 34W		35 3500K		BN Brush Nickel
CMED 6XX 12", 14", 16"			40 4000K		SN Satin Nickel
			50 5000K		CH Chrome

*Consult with factory for custom finishes

Example : CMED 513-23-830-P-WH

--	--	--	--	--