



DLED-166R

6" NON-IC, Remodel LED Frame-in Kit Downlight







14W, 22W, 33W & 43W LED, 120V ~ 277V Input




Catalog #		Type
Project		Date
Prepared by		

6" LED Remodel Frame-in Kit

 TML-169R Open Reflector	 TML-160B Baffle w/ Reflector	 TML-166B Baffle w/ Regressed Lens
 TML-166R Reflector w/ Regressed Lens	 TML-161 Wall Wash w/ Kick-off Plate	 TML-168 Reflector w/ Frosted Floating Lens

* All trims are rated for damp location, and regressed lens trims are for wet location listed.
 * Wide beam reflector is standard. Also available in other beam in reflector.(consult with factory)



SPECIFICATION				
LED Quantity	1EA (COB)			
Input Voltage	120V ~ 277V AC			
Wattage (Typ)	14 W	22 W	33 W	43 W
Lumen (Typ)	1,400	1,980	2,970	3,870
Efficacy (LPW)	100 lm/W	90 lm/W	90 lm/W	90 lm/W
Beam Angle	72.6°	75.5°	77°	76.2°
C R I (Typical)	80, 90			
Color (+/-5%)	2700K, 3000K, 3500K, 4000K, 5000K			
Dimming	Triac & 0-10V the both(Consult with factory for approved dimmers)			

- ### FEATURES and FUNCTIONS
- Mounting Frame : Galvanized steel.
 - Junction Box : Listed for through branch circuit wiring. (4 in, 4 out)
 - Heavy gauge aluminum reflector anodized in clear, haze, gold, champagne and pewter color finish.
 - Aluminum extruded Heat sink designed to facilitate heat dissipation.
 - Beam optic changeable with easy twist-on lock.
 - Easy-quick metal connector case supplied allowing easy and sturdier wire connector. (USA patented)
 - 120V~277V 60Hz Triac and 0-10V dimmable driver for most dimmers in the market.
 - 3 remodel clips secure housing and accommodates 1/2" and 5/8" ceiling materials.

Listing

- CSA-us & cETL
- Energy star Approved & Listed
- State of california Title 24
- Damp location

Warranty

- 5years of lamp life.

ORDERING INFORMATION

Housing	Watts	CRI	CCT	Driver	Trim	Reflector Finish	Baffle Finish	Optional Metal Trim Ring Finish
DLED-166R 6" Non-IC, Remodel LED Frame-in Kit	14 14W	8 80	27 2700K	UTD 120V, Triac Dimming (Standard) UZTD 120~277V, 0~10V Dimming	TML-169R	HC Haze Clear	WH White	WH White
	22 22W	9 90	30 3000K		TML-160B	WH White	BK Black	BK Black
	33 33W		35 3500K		TML-166B			
	43 43W		40 4000K		TML-166R			
			50 5000K		TML-161			
	*Option - EM=Emergency battery backup				TML-168	*Consult with factory for custom finishes		
Example : DLED-166R-22-830-UTD					Example : TML-169R-HC-WH			
<div><div></div> – <div></div> – <div></div> – <div></div></div>					<div><div></div> – <div></div> – <div></div></div>			