


LED Multiple Recessed Luminaire



MCLR-DOB 120V ~ 277V



Catalog #		Type
Project		Date
Prepared by		

1, 2, 3 or 4 lights 15W, 20W & 30W LED

ACCENT MULTIPLE LIGHTS WITH HIGH WATTAGE LED MODULES



Height : 5-1/2"

Ceiling Cut-out : 3-7/8"

Dimension Table

No. of Light	[1NL]	[2NL]	[3NL]	[4NL]
L (Length)	6-1/2" (164mm)	14" (365mm)	20-3/8" (518mm)	26-3/4" (680mm)

DESCRIPTION

MCLR series fixture is designed to be equivalent to standard PAR20 size lamp with skeleton frame allowing for installation in various ceiling application. It's the screw-down mechanism make it easier to install fixture with no tool required and sturdier mount. Mounted for new construction and remodeling.(direct to ceiling) Used advanced LED technology with AC module by customized IC embeded circuit on board for full dimming by most of Triac or 0-10V dimming switches in the market. Low heat, long life running from DOB technology can warrant more than 5years in weather change circumstances with (-30~+40) range.

SPECIFICATION

HOUSING	MCLR-DOB		
Input Voltage	120V-277V		
Wattage (+/-5%)	15W	20W	30W
Lumen (+/-5%)	975	1,300	1,950
Efficacy (LPW)	65 lm/W	65 lm/W	65 lm/W
CRI (Typical)	80, 90		
Color (+/-5%)	2700K, 3000K, 4000K, 5000K		
Dimming	Triac & 0-10V the both(Consult with factory for approved dimmers)		

FEATURES and FUNCTIONS

- Aluminum extruded frame integrated with 0.75" self flange around ceiling opening.
- Aluminum extruded Heat sink designed to facilitate heat dissipation.
- Spring loaded remodel clips allowing easy installation from below ceiling.
- (5)1/2" knockouts with true pry-out slots and (4) knockouts with Romex cable clamp.
- 120V~277V AC LED module with intergrated IC chip imbeded on a board.
- 0-10V dimming is standard.
- Overlap trim is standard.(Consult with factory in tremless.)

Listing

- CSA-us Certificated
- State of california Title 24
- Energy star Approved & Listed

Warranty

- 5years of lamp life.

ORDERING INFORMATION

Housing	No. of Light	Watt	CRI	CCT	Beam Angle	Trim Interior Finish	Options
MCLR-DOB Multiple Cluster LED Recessed Downlight	1LN (1) Light 2LN (2) Light 3LN (3) Light 4LN (4) Light	15 15W 20 20W 30 30W	8 80 9 90	27 2700K 30 3000K 40 4000K 50 5000K	N Narrow M Medium W Wide	WW White with White Flange BW Black with White Flange SW Silver with White Flange *Consult with factory for custom finishes	SNT Snoot LVR Louver HCL Hex Cell Louver LSN Linear Spread Lens LNS UV Lens ML Milk White Lens
Example : MCLR-DOB-1LN-15-830-M [] - [] - [] - [] - []						Example : BW []	