RTF3








Catalog #	Туре
outulog #	
Project	Date
Prepared by	


3" LED

120V, 220V-230V and 277V

3" LED Low Profile Surface Mount







DESCRIPTION

The surface Mount LED module is designed for use in ceiling flush mount and indoor wet location area. It can be installed onto a standard 3" J-Box with mounting bracket, easy to install the module by twist-in lock mechanism. Lumen output and distribution comparable to a 65 watts of electricity. Energy star qualified. Suitable for use with continuous room side temperature up to 40°C (104°F)

SPECIFICATION			
HOUSING	RTF3		
Wattage (Typ)	7W		
Lumen (Typ)	540(80CRI)		
Efficacy (LPW)	77 l m/W		
Beam Angle	100°		
CRI (Typical)	80, 90		
Color (+/-5%)	2700K, 3000K, 3500K, 4000K, 5000K		
Dimming	Triac(Consult with factory for approved dimmers)		

FEATURES and FUNCTIONS


- 120V AC LED module with integrated IC chip imbed on board and 10-100% Triac dimming with most of leading and trailing edge dimmer switches in the market.
- Driving circuit to prevent inrush current hurting dimmer switch and module.
- Recommended for use max. 30 lamps per run of 600W loaded dimmer switches and 15 lamps per dimmer switches 300W loaded.
- 90CRI Standard. Available in 2700K, 3000K, 3500K, 4000K and 5000K.
- Triac dimmable standard.

Listing

Warranty

- CSA-us Certificated
- Energy star Approved & Listed
- State of california Title 24
- Wet location
- 5years of lamp life.

J-Box Mounting



ORDERING INFORMATION

OIDELING IN ONIVATION				
Housing	CRI	ССТ	Finish	
RTF3 3", 7W	8 80	27 2700K	WH White	
	9 90	30 3000K	BK Black	
		35 3500K		
		40 4000K		
		50 5000K		
			*Consult with factory for custom finishes	

Example: RTF3-830-WH

