



**Spotstar Miniature**  
**120V, 220V-230V and 277V**  
 LED Pendant Lighting



Catalog #		Type
Project		Date
Prepared by		

**Pendant LED**

**LED  
 Pendant  
 Lighting**



**Dimension Table**

Housing	[ STS-2200P ]	[ STS-2300P ]	[ STS-2400P ]
Head D (Diameter)	2-1/8" (Ø55mm)	2-5/8" (Ø68mm)	3-1/2" (Ø87.5mm)
H (Height)	5-5/8" (144mm)	6-1/2" (163.5mm)	6-7/8" (174.5mm)

**DESCRIPTION**

In this family of Spotstar, this pendant lighting. Spotstar Miniature offers superior output in a small, sleek design allowing spot beam to each object. Designed for optimized optical and thermal management in a slender diecast housing.

**FEATURES and FUNCTIONS**

- One piece casted aluminum and heat sink designed to facilitate heat dissipation.
- Exchangeable reflector for beam angle, 25 and 40 degree.
- 120V~277V AC LED module integrated IC chip imbed on board.
- Available in stem rod or aircraft cable in various lengths.
- 80 CRI, 2700K, 3000K, 3500K, 4000K and 5000K
- Hanging aircraft cable is standard. Stem rod is available(optional).
- Triac dimming is standard.

**Listing**

- CSA-us Certificated
- State of California Title 24
- Energy star Approved & Listed

**Warranty**

- 5years of lamp life.

**SPECIFICATION**

HOUSING	STS-2200P		STS-2300P			STS-2400P		
Wattage (Typ)	10W	15W	15W	20W	30W	15W	20W	30W
Lumen (Typ)	600	907	975	1,304	1,950	870	1,160	1,732
Efficacy (LPW)	60 lm/W	60.5 lm/W	65 lm/W	65 lm/W	65 lm/W	58 lm/W	58 lm/W	58 lm/W
Beam Angle	25° / 40°							
C R I (Typical)	80							
Color (+/-5%)	2700K, 3000K, 3500K, 4000K, 5000K							
Dimming	Triac & 0-10V the both(Consult with factory for approved dimmers)							

**ORDERING INFORMATION**

Housing	Watts	CRI	CCT	Beam Angle	Aircraft Cable Length	Finish
STS-2200P	10 10W	8 80	27 2700K	25 25°	12 12 Inches	WH White BK Black
STS-2300P	15 15W		30 3000K	40 40°	18 18 Inches	
STS-2400P	20 20W		35 3500K		24 24 Inches	
	30 30W		40 4000K		36 36 Inches	
			50 5000K		48 48 Inches	

\*Consult with factory for custom finishes

Example : STS-2200P-10-830-25-12-BK

-  -  -  -  -