UCLD(T)







Catalog #	Туре
Project	Date
Prepared by	

LED Undercabinet Light

120V, 220V-230V and 277V

Linear LED



a O	0	0	0	
				3.3/4"
				3-3/4" (95mm)
	L			1-1/16" (27mm)

FEATURES and FUNCTIONS

- Assembled by aluminum body, flip cover and plastic lens.
- Plastic end caps provided male and female receptacles for power cord and link cable connector or direct connector for linking end to end, locker switch on cover plate.
- 120V AC LED module with integrated IC chip imbed on board and 10-100% triac dimmable with most of leading and trailing edge dimmer switches in the market
- Listed for both of portable lamp type (UL153) with power cord set and permanent hardwire type (UL1598) with knock outs for 1/2" trade size conduit and Romex cable in end cap and backside.
- Various length of models as in specification with different wattages from 4W(9"L) through 17W(48"L).
- Optional-available in color temperature selectable(3000K, 4000K, 5000K).
- Long life (5years warranty) as of no trouble with driver.

Optional Accessories

- 6ft power cord set.
- 6" flexible wire with both ends connectors.

SPECIFICATION					
Housing	L (Length)	Watts	Lumen		
UCLD(T) 0903	9" (230mm)	4W	200 l m		
UCLD(T) 1204	12" (305mm)	5W	270 l m		
UCLD(T) 1807	18" (460mm)	7W	420 l m		
UCLD(T) 2108	21" (534mm)	8W	460 l m		
UCLD(T) 2409	24" (610mm)	9W	580 l m		
UCLD(T) 3612	36" (915mm)	13W	800 l m		
UCLD(T) 4818	48" (1,220mm)	17W	1,070 l m		


Listing

- CSA-us Certificated
- Energy star Approved & Listed
- State of california Title 24

Warranty

• 5years of lamp life.

Linkable



ORDERING INFORMATION

* Consult with factory for approved dimmers

Housing		CRI CCT		Finish		
UCLD	0903 9", 4W	3612 36", 13W	8 80	27 2700K	WH White Painted	
UCLDT CCT Selectable	1204 12", 5W	4818 48", 17W	9 90	30 3000K	BK Black Painted	
	1807 18", 7W			35 3500K	AL Aluminum	
	2108 21", 8W			40 4000K	BZ Bronze Painted	
	2409 24", 9W			50 5000K		
*Consult with factory for CCT range						*Consult with factory for custom finishes
Example : UCLD 1807-840-WH						·