


# OUTDOOR Light

## WCED-4S(U)D(P)

120V, 220V-230V and 277V

4" Square LED Wall & Pendant Mount Cylinder Light (Up/Down & Down Type)



Catalog #		Type
Project		Date
Prepared by		


### 4" Square LED Cylinder



**WCED-4SD**  
(DOWN TYPE)

**WCED-4SUD**  
(UP/DOWN TYPE)

**WCED-4SDP**  
(PENDANT DOWN TYPE)



[ WCED-4SD ]

[ WCED-4SUD ]

#### DESCRIPTION

Wet location(IP65) rated outdoor use square cylinder type wall or pendant mount with downlight and up & down light. 13W, 17W and 27W LED AC module by customized IC, embedded circuit on board for full (5% lowest) dimming by most of Triac or 0-10V dimming switches in the market. Low heat, long life running from DOB technology can warrant more than 5 years in weather change circumstances with (-30°C ~ +40°C) range.

#### SPECIFICATION

HOUSING	WCED-4S(U)D(P)		
Wattage (Typ)	13W	17W	27W
Lumen (Typ)	910(80CRI)	1,190(80CRI)	1,890(80CRI)
Efficacy (LPW)	70 lm/W	70 lm/W	70 lm/W
Beam Angle	11° / 22° / 37°		
CRI (Typical)	80, 90		
Color (+/-5%)	2700K, 3000K, 3500K, 4000K, 5000K		
Dimming	Triac & 0-10V the both(Consult with factory for approved dimmers)		

#### FEATURES and FUNCTIONS

- Main body by weather proof aluminum powder coated white, black and silver finish for outdoor/indoor applications
- 13W, 17W and 27W 120V DOB modules with integrated circuit on board with customized chips (No driver needed)
- Hanging aircraft cable is standard. Also available in stem rod(For down type only)
- Also available in photocell sensor and day light harvest.
- 80, 90 CRI, 2700K, 3000K, 3500K, 4000K and 5000K
- Triac dimming is standard. Also available 0-10V dimming.

#### Listing

- CSA-us Certificated
- State of california Title 24
- Energy star Approved & Listed
- Wet location (IP65 Rated)

#### Provided

- SENSOR



#### Warranty

- 5years of lamp life.

#### ORDERING INFORMATION

Housing	Watts	CRI	CCT	Beam Angle	Housing Finish	Aircraft Cable Length	Option
<b>WCED-4SD</b> Down Type	<b>13</b> 13W	<b>8</b> 80	<b>27</b> 2700K	<b>N</b> 11°	<b>WH</b> White	<b>12</b> 12 Inches	<b>PCR</b> Photocell Sensor
<b>WCED-4SUD</b> Up / Down Type	<b>17</b> 17W	<b>9</b> 90	<b>30</b> 3000K	<b>M</b> 22°	<b>BK</b> Black	<b>18</b> 18 Inches	
<b>WCED-4SDP</b> Pendant Down Type	<b>27</b> 27W		<b>35</b> 3500K	<b>W</b> 37°	<b>SI</b> Silver	<b>24</b> 24 Inches	
			<b>40</b> 4000K			<b>36</b> 36 Inches	
			<b>50</b> 5000K			<b>48</b> 48 Inches	
					*Consult with factory for custom finishes	*For pendant Mount Only	

Example : WCED-4SDP-27-840-W-BK-48

-  -  -  -  -