


OUTDOOR Light WPD(L)

120V ~ 277V, 0-10V Dimmable

LED Wall Pack



Catalog #


Project

Prepared by

Type


Date

Wall LED




11"
(280mm)

[WPD]




6-3/4"
(170mm)

5-1/8"
(130mm)



16-1/8"
(410mm)

[WPD(L)]



9-1/2"
(241mm)

6-5/8"
(167mm)

DESCRIPTION

ISLT standard WPD Wall Pack with AC direct DOB solution with slim size allowing better light distribution with specially designed glass diffuser to shatter deliver light uniformity. It's suitable for outdoor environments in parking garage, public area, school etc.

SPECIFICATION

HOUSING	WPD		WPD(L)	
Wattage (Typ)	45W	70W	100W	120W
Lumen (Typ)	4,050(80CRI)	6,300(80CRI)	9,000(80CRI)	10,800(80CRI)
Efficacy (LPW)	90 lm/W	90 lm/W	90 lm/W	90 lm/W
CRI (Typical)	80, 90			
Color (+/-5%)	4000K, 5000K, 5700K			
Dimming	0-10V(Consult with factory for approved dimmers)			

FEATURES and FUNCTIONS

- Slim and compact design.
- Durable die cast housing with fully seated with silicone gasket allowing waterproof and bug-free.
- High quality heat treated glass.
- 120~277V AC LED module with integrated IC chip imbed on board.
- Die cast housing and the heat sink to facilitate heat dissipation.
- Designed for wall mounting to hard wires in Junction box.
- 0-10V dimming is standard.
- Micro wave sensor and Emergency battery backup available. (Consult with factory.)

Listing

- CSA-us Certificated
- State of california Title 24
- DLC qualified
- Wet location


Warranty

- 5years of lamp life.

ORDERING INFORMATION

Housing	CRI	CCT	Finish	Options
WPD-45 11", 45W	8 80	40 4000K	WH White	MS Motion Sensor
WPD-70 11", 70W	9 90	50 5000K	BK Black	BB Battery Backup
WPD(L)-100 16", 100W		57 5700K	BN Brush Nickel	WGuard Wire Guard
WPD(L)-120 16", 120W			BZ Bronze	

*Consult with factory for custom finishes



Example : WPD-45-840-BK

- -